

Roulement conique 622A-612A-TIMKEN - 622A-612A-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/622a-612a-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|---------|---------|--|----------------------------|---|----------------------------|--------------------------|-------|-------------|------|------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ K | Dynamic ⁽³⁾ C ₀₁ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 55.006 | 120.040 | 41.275 | 201900 | 2.31 | 1.01 | 53900 | 20000 | 1.88 | 244000 | 622A | 612A |
| 2.1830 | 4.7260 | 1.6250 | 48000 | | | 12100 | 6510 | | 54800 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|---|--------------------------------------|---|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max. Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | | | | | | |
| 41.275 | 31.250 | -14.8 | 0.8 | 64.8 | 65.8 | 3.3 | 118.8 | 193.8 | 3.8 | 1.8 | 75.9 | 16.2 | 0.0064 | 2.13 |
| 1.6250 | 1.2500 | -0.35 | 0.03 | 2.52 | 2.35 | 0.13 | 4.33 | 4.06 | 0.15 | 0.09 | | | | 4.72 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952317595 |
| Diam. intérieur | 55.006 mm |
| Diam. extérieur | 120.04 mm |
| Épaisseur | 41.275 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE