

## Roulement conique 3982X-3927AS-TIMKEN - 3982X-3927AS-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/3982x-3927as-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> Y	Dynamic <sup>3)</sup> C <sub>2</sub>	Factor <sup>4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
63.500	116.000	29.370	139000	1.40	30000	24000	1.45	191000	292X	3927AS
2.5000	4.3307	1.1563	21200		8000	1010		43000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>1)</sup>	Max Shaft Fillet Radius R <sub>1</sub> <sup>2)</sup>	Backing Shoulder Dia. d <sub>s</sub> <sup>3)</sup>	Max Housing Fillet Radius r <sup>4)</sup>	Backing Shoulder Dia. D <sub>s</sub> <sup>5)</sup>	A <sub>1</sub> <sup>6)</sup>	A <sub>2</sub> <sup>7)</sup>	A <sub>3</sub> <sup>8)</sup>				kg	
30.48	23.020	-4.6	7.6	71.6	84.8	0.5	105.0	101.0	2.2	1.2	75.2	21.3	0.1002	1.10
1.1920	0.9063	-0.18	0.29	2.80	3.31	0.02	4.13	3.94	0.08	0.05				2.43

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952319124
Diam. intérieur	63.5 mm
Diam. intérieur	2 1/2" inch
Diam. extérieur	110 mm
Diam. extérieur	4.331" inch
Epaisseur	29.37 mm
Epaisseur	1 5/32" inch
Conditionnement	1
Norme	Sans norme

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE