


## Roulement conique

### H715336-H715310-TIMKEN - H715336-H715310-TIMKEN

https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/h715336-h715310-timken

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |         |         | Load Ratings                             |                            |                            |   |                            |                          | Part Number |         |         |
|--------------------|---------|---------|--|----------------------------|----------------------------|---|----------------------------|--------------------------|-------------|---------|---------|
| Bore d             | O.D. D  | Width T | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factor <sup>(2)</sup><br>e | Factor <sup>(3)</sup><br>f | Dynamic <sup>(1)</sup><br>C <sub>02</sub> | Factor <sup>(3)</sup><br>K | Static<br>C <sub>0</sub> | Inner       | Outer   |         |
| mm                 | mm      | mm      | N  |                            |                            | N   |                            | N                        |             |         |         |
| 63.500             | 139.700 | 46.038  | 219000                                   | 2.97                       | 1.27                       | 82700                                     | 67000                      | 1.24                     | 400000      | H715336 | H715310 |
| 2.5000             | 5.5000  | 1.8125  | 71700                                    |                            |                            | 19600                                     | 15100                      |                          | 91000       |         |         |

| Bearing Dimensions |         |                          |  |                                      |  |                                      |                               |                               |                               | Geometry Factors |                |                | Bearing Weight |      |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|------|
| Shaft              |         |                          |  |                                      | Housing                                    |                                      |                               |                               |                               | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> |                |      |
| Width B            | Width C | ER. Dr. α <sup>(1)</sup> | Max Shaft Fillet Radius R <sup>(2)</sup> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sup>(2)</sup> | Backing Shoulder Dia. D <sub>s</sub> | A <sub>1</sub> <sup>(3)</sup> | A <sub>2</sub> <sup>(3)</sup> | A <sub>3</sub> <sup>(3)</sup> |                  |                |                | kg             |      |
| 46.038             | 36.512  | -8.6                     | 3.5                                      | 82.8                                 | 88.8                                       | 3.3                                  | 133.8                         | 120.8                         | 4.1                           | 2.8              | 147.1          | 35.5           | 0.0983         | 3.89 |
| 1.8125             | 1.4375  | -0.34                    | 0.14                                     | 3.23                                 | 3.45                                       | 0.13                                 | 5.24                          | 4.72                          | 0.16                          | 0.09             |                |                |                | 7.93 |

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | TIMKEN        |
| N° Ean13        | 3663952319506 |
| Diam. intérieur | 63.5 mm       |
| Diam. extérieur | 139.7 mm      |
| Épaisseur       | 46.038 mm     |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE