


Roulement conique 6466-6420-TIMKEN - 6466-6420-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/6466-6420-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | Part Number | |
|--------------------|---------|---------|--------------------------------------|------------------------|---------------------------------------|------------------------|-----------------------|-------------|-------|
| Bore d | O.D. D | Width T | Dynamic ¹⁾ C ₁ | Factor ²⁾ e | Dynamic ³⁾ C ₀₂ | Factor ⁴⁾ K | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | | N | | N | | |
| 76.200 | 149.225 | 53.975 | 41100 | 2.30 | 10700 | 1.61 | 40300 | 6466 | 6420 |
| 3.0000 | 5.8750 | 2.1250 | 5250 | | 2400 | | 10400 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|-------------------------|--|--------------------------------------|--|--------------------------------------|------------------------------|------------------------------|------|------------------|----------------|----------------|----------------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | |
| Width B | Width C | ER. Dr. α ¹⁾ | Max. Shaft Fillet Radius R ²⁾ | Backing Shoulder Dia. d _s | Max. Housing Fillet Radius r ³⁾ | Backing Shoulder Dia. D _s | A ₁ ⁴⁾ | A ₂ ⁵⁾ | Cage | | | | kg |
| 54.225 | 44.400 | -15.8 | 0.4 | 88.8 | 3.3 | 140.8 | 2.7 | 8.7 | 0.10 | 158.3 | 20.1 | 0.001 | 4.22 |
| 2.1250 | 1.7300 | -0.58 | 0.25 | 3.52 | 0.13 | 5.51 | 5.08 | 0.10 | 0.03 | | | | 9.30 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952321646 |
| Diam. intérieur | 76.2 mm |
| Diam. intérieur | 3" inch |
| Diam. extérieur | 149.225 mm |
| Diam. extérieur | 5 7/8" inch |
| Epaisseur | 53.975 mm |
| Epaisseur | 2 1/8" inch |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE