

Roulement conique 6576-6525X-TIMKEN - 6576-6525X-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/6576-6525x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|-------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 76.200 | 160.000 | 53.975 | 42900 | 2.40 | 114000 | 26900 | 1.46 | 52300 | 6576 | 6525X |
| 2.0000 | 8.2900 | 2.1250 | 9800 | | 29500 | 13900 | | 118000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|---|--------------------------------------|---|--------------------------------------|------------------------------------|-------------------------------|------|------------------|----------------|----------------|----------------|-------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max. Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d _s | Max. Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D _s | Cage A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | | | | | | |
| 55.100 | 66.450 | -13.2 | 3.5 | 92.8 | 95.8 | 3.0 | 153.4 | 141.8 | 4.1 | 6.8 | 198.6 | 33.5 | 0.1027 | 6.26 |
| 2.1933 | 1.7500 | -0.52 | 0.14 | 3.62 | 3.90 | 0.12 | 6.04 | 5.55 | 0.16 | 0.04 | | | | 11.80 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952321707 |
| Diam. intérieur | 76.2 mm |
| Diam. extérieur | 160 mm |
| Épaisseur | 53.975 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE