

## Roulement conique 47681-47620-TIMKEN - 47681-47620-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/47681-47620-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> F	Dynamic <sup>3)</sup> C <sub>02</sub>	Factor <sup>4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
80.962	133.350	33.338	214000	1.40	55000	20000	1.44	262000	47681	47620
3.1875	5.2500	1.3125	48100		12500	8040		58600		

  

Bearing Dimensions										Geometry Factors			Bearing Weight		
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>				
Width B	Width C	ER. Dr. a <sup>1)</sup>	Max. Shaft Fillet Radius R <sup>2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sup>3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>4)</sup>	A <sub>2</sub> <sup>5)</sup>							kg
33.338	26.195	-4.3	0.5	89.8	0.8	35.8	3.3	128.8	118.8	2.3	2.4	115.4	29.2	0.1273	1.36
1.3125	1.0313	-0.17	0.14	3.50	3.74	0.13	5.04	4.89	0.09	0.10					3.86

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3616060456571
Diam. intérieur	80.962 mm
Diam. intérieur	3 3/16" inch
Diam. extérieur	133.35 mm
Diam. extérieur	5 1/4" inch
Epaisseur	33.338 mm
Epaisseur	1 5/16" inch
Poids	1698 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE