

Roulement conique 81600-81962-TIMKEN - 81600-81962-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/81600-81962-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|--------------------------------------|------------------------|---------------------------------------|------------------------|-----------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ¹⁾ C ₁ | Factor ²⁾ Y | Dynamic ³⁾ C ₀₂ | Factor ⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 152.400 | 244.425 | 47.625 | 40200 | 1.35 | 10900 | 1.66 | 59500 | 81600 | 81962 | |
| 6.000 | 8.820 | 1.875 | 9200 | | 2340 | | 12400 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | | |
|--------------------|---------|-------------------------|--|--------------------------------------|--|--------------------------------------|------------------------------|------------------------------|------------------------------|------------------|----------------|----------------|------------------------------|------------------------------|------------------------------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. a ¹⁾ | Min. Shaft Fillet Radius R ²⁾ | Backing Shoulder Dia. d ₄ | Max. Housing Fillet Radius r ³⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁴⁾ | A ₂ ⁵⁾ | A ₃ ⁶⁾ | | | | A ₄ ⁷⁾ | A ₅ ⁸⁾ | A ₆ ⁹⁾ |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| 50.085 | 33.336 | -5.3 | 3.5 | 195.9 | 176.9 | 3.3 | 225.1 | 225.0 | 8.2 | * | 413.0 | 98.4 | 0.1250 | 7.88 | 16.91 |
| 1.9687 | 1.3125 | -0.21 | 0.14 | 6.90 | 6.73 | 0.13 | 9.02 | 8.86 | 0.32 | * | | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952325996 |
| Diam. intérieur | 152.4 mm |
| Diam. extérieur | 244.475 mm |
| Épaisseur | 47.625 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE