


## Roulement conique 88925-88126-TIMKEN - 88925-88126-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/88925-88126-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |         |         | Load Ratings                         |                        |                                       |                        |                       |       | Part Number |  |
|--------------------|---------|---------|--------------------------------------|------------------------|---------------------------------------|------------------------|-----------------------|-------|-------------|--|
| Bore d             | O.D. D  | Width T | Dynamic <sup>1)</sup> C <sub>1</sub> | Factor <sup>2)</sup> e | Dynamic <sup>3)</sup> C <sub>02</sub> | Factor <sup>3)</sup> K | Static C <sub>0</sub> | Inner | Outer       |  |
| mm                 | mm      | mm      | N                                    |                        | N                                     |                        | N                     |       |             |  |
| 234.950            | 320.675 | 50.800  | 92900                                | 2.40                   | 143000                                | 119000                 | 821000                | 88125 | 88126       |  |
| 9.2500             | 12.6250 | 2.0000  | 124500                               |                        | 32200                                 | 26800                  | 189000                |       |             |  |

| Bearing Dimensions |         |                         |  |                                      |  |                                      |                |                              |                              | Geometry Factors |                |                | Bearing Weights              |                |
|--------------------|---------|-------------------------|--|--------------------------------------|--|--------------------------------------|----------------|------------------------------|------------------------------|------------------|----------------|----------------|------------------------------|----------------|
| Shaft              |         |                         |  |                                      | Housing                                    |                                      |                |                              |                              | Cage             | G <sub>1</sub> | G <sub>2</sub> |                              | C <sub>3</sub> |
| Width B            | Width C | ER. Dr. α <sup>1)</sup> | Min. Shaft Fillet Radius R <sup>2)</sup> | Backing Shoulder Dia. d <sub>1</sub> | Max. Housing Fillet Radius r <sup>3)</sup> | Backing Shoulder Dia. D <sub>1</sub> | D <sub>2</sub> | A <sub>1</sub> <sup>4)</sup> | A <sub>2</sub> <sup>5)</sup> |                  |                |                | A <sub>3</sub> <sup>6)</sup> |                |
| mm                 | mm      | mm                      | mm                                       | mm                                   | mm   | mm                                   | mm             | mm                           | mm                           | mm               | mm             | mm             | mm                           | mm             |
| in.                | in.     | in.                     | in.                                      | in.                                  | in.  | in.                                  | in.            | in.                          | in.                          | in.              | in.            | in.            | in.                          | in.            |
| 40.212             | 33.336  | 14.2                    | 6.4                                      | 246.0                                | 258.0                                      | 3.3                                  | 309.0          | 290.0                        | 11.1                         | 2.7              | 0.601          | 1.081          | 0.1362                       | 10.12          |
| 1.5835             | 1.3125  | 0.56                    | 0.25                                     | 9.69                                 | 10.16                                      | 0.13                                 | 12.17          | 11.77                        | 0.43                         | 0.11             |                |                |                              | 22.21          |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | TIMKEN        |
| N° Ean13        | 3663952327839 |
| Diam. intérieur | 234.95 mm     |
| Diam. intérieur | 9 1/4" inch   |
| Diam. extérieur | 320.675 mm    |
| Diam. extérieur | 12 5/8" inch  |
| Epaisseur       | 50.8 mm       |
| Epaisseur       | 2" inch       |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE