

# Roulement conique EE941205X-941950-TIMKEN - EE941205X-941950-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/ee941205x-941950-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Static <sup>(2)</sup> C <sub>2</sub>	Dynamic <sup>(3)</sup> C <sub>3</sub>	Static <sup>(4)</sup> C <sub>4</sub>	Dynamic <sup>(5)</sup> C <sub>5</sub>	Static <sup>(6)</sup> C <sub>6</sub>	Inner	Outer	
mm	mm	mm	N	N	N	N	N	N			
304.800	495.300	76.200	150000	210	1.45	40000	27000	1.45	209000	EE941205X	941950
12.000	19.500	3.000	348000			9000	6200		47000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight							
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>						
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max. Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(2)</sup>	A <sub>2</sub> <sup>(3)</sup>	A <sub>3</sub> <sup>(4)</sup>				A <sub>4</sub> <sup>(5)</sup>		A <sub>5</sub> <sup>(6)</sup>	A <sub>6</sub> <sup>(7)</sup>	A <sub>7</sub> <sup>(8)</sup>	A <sub>8</sub> <sup>(9)</sup>	A <sub>9</sub> <sup>(10)</sup>	A <sub>10</sub> <sup>(11)</sup>
77.866	53.975	5.1	6.4	352.0	326.8	3.3	462.7	498.0	16.2	2.3	0.40	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11
3.0666	2.1250	0.20	0.25	13.87	12.95	0.13	18.22	19.87	0.64	0.09	0.016	0.0044	0.0044	0.0044	0.0044	0.0044	0.0044	0.0044	0.0044	0.0044

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952329321
Diam. intérieur	304.8 mm
Diam. intérieur	12" inch
Diam. extérieur	495.3 mm
Diam. extérieur	19 1/2" inch
Epaisseur	76.2 mm
Epaisseur	3" inch
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE