

Roulement à bille simple rangée ZKLN3072-2Z-INA - ZKLN3072-2Z-INA

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/zkln3072-2z-ina>

Axial angular contact ball bearings ZKLN3072-2Z
double direction, gap seals on both sides

d	30 mm	Tolerance: -0.005
D	72 mm	Tolerance: -0.010
B	38 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{a,max}	64 mm	
d₁	51 mm	
d_{2,min}	47 mm	
f_{1,max}	0.6 mm	
f_{2,min}	0.3 mm	
m	0.72 kg	Mass
C_d	35000 N	Basic dynamic load rating, axial
C_{0,ax}	13600 N	Basic static load rating, axial
n_{0,ax}	4000 1/min	Limiting speed for grease lubrication
M_{0,ax}	0.4 Nm	Bearing frictional torque
c_{ax}	950 N/mm	Axial rigidity
c_{ax}	400 Nm/mrad	Tilting rigidity
M_x	1.91 kg x cm ²	Mass moment of inertia for rotating inner ring
r_{ax}	2.5 μm	Axial runout
ZMA30/52		Designation of recommended INA locknut
AM30		Designation of recommended INA locknut
M_t	65 Nm	Tightening torque
	19509 N	Axial preload force

CARACTÉRISTIQUES PRODUIT

Marque	INA
N° Ean13	3663952334905
Diam. intérieur	30 mm
Etanchéité	Flasque des deux côtés
Diam. extérieur	72 mm
Epaisseur	38 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE