

Roulement conique 3387-3320-B-TIMKEN - 3387-3320-B-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/3387-3320-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | | | | | | | Load Ratings | | | | Part Number | |
|--------------------|-----------|------------|---|-----------------------------|---|-----------------------------|--------------------------|-------|-------|--------------|--|--|--|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁₀ | Factors ⁽¹⁾ e | Dynamic ⁽²⁾ C ₉₀ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | | | | | |
| mm | mm | mm | N | | N | | N | | | | | | | | |
| 38.130 | 80.167 | 10.320 | 115000 | 0.37 | 23800 | 1300 | 2.14 | 12800 | 3387 | 3320-B | | | | | |
| 1.500 | 3.182 | 0.408 | 2500 | | 6700 | 3100 | | 29100 | | | | | | | |

| Bearing Dimensions | | | | | | | | | | Shaft | | | Housing | | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-----------------------------|--|-----------------------------------|--|--|--|--|----------------|----------------|----------------|--|---------|--|--|------------------|------|--|----------------|
| Width B | Width C | Eff. Dia. d ₁ | Outer Ring Ridge O.D. D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽¹⁾ | Seaking Shoulder Dia. d ₂ | Seaking Shoulder Dia. D ₂ | Seaking Shoulder Dia. D ₃ | G ₁ | G ₂ | C ₂ | | | | | | kg | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | | | | | | | |
| 30.301 | 23.812 | -18.0 | 84.026 | 4.302 | 0.8 | 46.5 | 46.6 | 77.0 | 34.6 | 12.1 | 0.0144 | | | | | | 0.75 | | |
| 1.1965 | 0.9375 | -0.43 | 3.3368 | 0.1675 | 0.03 | 1.75 | 1.77 | 3.03 | | | | | | | | | 1.63 | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952336497 |
| Diam. intérieur | 38.1 mm |
| Diam. extérieur | 80.167 mm |
| Épaisseur | 10.32 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE