


# Roulement conique XGA33210-YSA33210R-TIMKEN - XGA33210-YSA33210R-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/xga33210-ysa33210r-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



| Bearing Dimensions |           |            | Load Ratings                             |                             |   |                             |                          |       |          | Part Number |  |
|--------------------|-----------|------------|--|-----------------------------|---|-----------------------------|--------------------------|-------|----------|-------------|--|
| Bore<br>d          | O.D.<br>D | Width<br>B | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factors <sup>(1)</sup><br>e | Dynamic <sup>(2)</sup><br>C <sub>02</sub> | Factors <sup>(2)</sup><br>K | Static<br>C <sub>0</sub> | Inner | Outer    |             |  |
| mm                 | mm        | mm         | N  |                             | N   |                             | N                        |       |          |             |  |
| 40                 | 95        | 29.9       | 15400                                    | 0.4                         | 1.45                                      | 2050                        | 2.2                      | 16800 | XGA33210 | YSA33210R   |  |
| 1.5748             | 3.7402    | 1.1772     | 24000                                    |                             | 8900                                      | 6300                        | 1.41                     | 37500 |          |             |  |

| Bearing Dimensions |            |                             | Shaft                                      |                                   |   | Housing                                    |  |                | Geometry Factors |                |        | Bearing Weight |
|--------------------|------------|-----------------------------|--|-----------------------------------|---|--|--|----------------|------------------|----------------|--------|----------------|
| Width<br>B         | Width<br>C | Eff. Dia.<br>d <sub>2</sub> | Outer Ring<br>Ridge O.D.<br>D <sub>2</sub> | Flange<br>Width<br>C <sub>1</sub> | Max Shaft<br>File Radius<br>(R <sub>1</sub> ) | Sealing<br>Shoulder Dia.<br>d <sub>3</sub> | Sealing<br>Shoulder Dia.<br>D <sub>3</sub> | G <sub>1</sub> | G <sub>2</sub>   | C <sub>2</sub> |        |                |
| mm                 | mm         | mm                          | mm   | mm                                | mm  | mm   | mm   |                |                  |                | kg     |                |
| 29.9               | 27.96      | -4.6                        | 102.900                                    | 5.800                             | 1.5   | 54.0                                       | 55.0                                       | 89.0           | 48.4             | 16.9           | 0.0957 | 1.25           |
| 1.1772             | 1.1008     | -0.34                       | 4.07157                                    | 0.1968                            | 0.06  | 2.13                                       | 2.20                                       | 3.50           |                  |                |        | 2.70           |

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | TIMKEN        |
| N° Ean13        | 3663952336701 |
| Diam. intérieur | 40 mm         |
| Diam. extérieur | 95 mm         |
| Épaisseur       | 29.9 mm       |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE