

Roulement conique 3778-3720-B-TIMKEN - 3778-3720-B-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/3778-3720-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|---|-----------------------------|--------------------------|-------|-------|------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽¹⁾ e | Dynamic ⁽²⁾ C ₀₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | | |
| mm | mm | mm | N | | N | | N | | | | | |
| 47.625 | 93.264 | 11.112 | 12200 | 0.24 | 1.77 | 31700 | 10000 | 1.70 | 13300 | 3778 | 3720-B | |
| 1.8750 | 3.6718 | 0.4375 | 2750 | | 7120 | | 4120 | | 34200 | | | |

| Bearing Dimensions | | | | Shaft | | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-----------------------------|--|-----------------------------------|---|--|--|--|----------------|------------------|----------------|--|----------------|
| Width B | Width C | Eff. Dia. d ₁ | Outer Ring Ridge O.D. D ₁ | Flange Width C ₁ | Max Shaft File Radius (R ₁) | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. d ₃ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁ | | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | lbs |
| 30.302 | 23.812 | -4.1 | 97.803 | 4.702 | 0.4 | 56.6 | 67.8 | 89.3 | 49.9 | 14.5 | 0.0903 | | 0.96 |
| 1.1920 | 0.9375 | -0.32 | 3.8558 | 0.1875 | 0.25 | 2.17 | 2.64 | 3.54 | | | | | 2.12 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952337388 |
| Diam. intérieur | 47.625 mm |
| Diam. extérieur | 93.264 mm |
| Épaisseur | 30.302 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE