

Douille à aiguilles
TLAM1812-IKO - TLAM1812-IKO

https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/tlam1812-iko



SHELL TYPE NEEDLE ROLLER BEARINGS



TAM TLAM

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
18	---	---	---	---	---	---	---	---	---	---
TLAM 1812								13.7	---	---

Boundary dimensions mm				Standard mounting dimensions mm								Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring IRT 1512
F _w	D	C	i ₂ Max.	Shaft dia. H7		Housing bore dia. N7		J7		N7					
				Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.				
18	24	12	1.3	18.000	17.989	---	---	23.993	23.972	8 230	11 500	20 000	IRT 1512		

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952352978
Diam. intérieur	18 mm
Diam. extérieur	24 mm
Epaisseur	12 mm
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE