


Douille à aiguilles YT1715-IKO - YT1715-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/yt1715-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number								Grease retained Mass (Ref.) g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g			
17	—	—	—	—	—	—	—	—	—	YT 1715	20.5

Boundary dimensions mm				Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	t ₂ Max.	Shaft dia. H7		Housing bore dia. N7				N	N	rpm	
				Max.	Min.	Max.	Min.	Max.	Min.				
17	24	15	—	17.000	16.989	24.012	23.991	—	—	16 600	26 000	9 000	IRT 1215-2

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952353135
Diam. intérieur	17 mm
Diam. extérieur	24 mm
Épaisseur	15 mm
Poids	22 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE