

## Roulement conique 32936-TIMKEN - 32936-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32936-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> Y	Dynamic <sup>(3)</sup> C <sub>0</sub>	Factor <sup>(3)</sup> C <sub>0e</sub>	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
180.000	250.000	45.000	403000	0.48	1.25	130000	80900	1.22	795000	32936
7.0000	5.8425	1.7717	10000			22000	18300		179000	

  

Bearing Dimensions										Geometry Factors			Bearing Weight		
Shaft					Housing					Cage					
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Shoulder Dia. d <sub>e</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>e</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
45.000	34.000	0.9	2.5	182.0	186.0	2.0	182.0	201.0	4.0	2.3	801.0	184.0	0.1208	6.40	
1.7717	1.3288	0.35	0.13	7.56	7.72	0.08	6.87	8.09	0.15	0.09				14.27	

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952354095
Diam. intérieur	180 mm
Diam. extérieur	250 mm
Épaisseur	45 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE