

## Roulement conique 32048X-TIMKEN - 32048X-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32048x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynami <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(1)</sup> Y	Dynami <sup>(2)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
in.	in.	in.	lbf		lbf	lbf	lbf			
240.000	360.000	76.000	1180000	0.42	206000	241000	1200000	32048X		
9.4489	14.1732	2.9921	265000		68000	54100	430000			

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shift Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Fillet Radius r <sup>(1)</sup>	Max Housing Fillet Radius D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	lbs.	
76.000	57.000	2.2	4.0	250.0	200.0	3.0	300.0	200.0	16.5	4.4	1305.0	145.0	0.1010	22.25
2.9921	2.2441	0.08	0.16	10.20	10.16	0.12	13.82	13.03	0.41	0.17				0.11

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952354163
Diam. intérieur	240 mm
Diam. intérieur	9.449" inch
Diam. extérieur	360 mm
Diam. extérieur	14.173" inch
Epaisseur	76 mm
Epaisseur	2.992" inch
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE