

## Roulement conique 390A-394D-TIMKEN - 390A-394D-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/390a-394d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Y <sub>2</sub>	C <sub>0</sub>	Dynamic <sup>(1)</sup> C <sub>90</sub>	Factor <sup>(2)</sup> K		
mm	mm	mm	mm	N			N	N			
63.500	110.000	52.388	46.020	12500	0.40	1.08	2.50	25000	17000		
2.500	4.3307	2.0625	1.8126	38700			5700	3970	10000		

  

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>			kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
390A	394D	1.5	73.0	0.8	106.4	-	-	50.0	21.4	0.0864	1.00			4.18	
		0.06	2.87	0.05	4.11										

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952356983
Diam. intérieur	63.5 mm
Diam. extérieur	110 mm
Epaisseur	52.388 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE