


Douille à aiguilles TAW6545-Z-IKO - TAW6545-Z-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/taw6545-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number								Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g				
65	TAW 6545 Z	290	—	—	—	—	—	—	88 300	207 000	4 000	IRT 5545

Boundary dimensions mm			Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring	
F _w	D	C	Shaft dia. d		Housing bore dia. D		N ₁	N ₂					
65	77	45	f ₂ Max.	Max.	Min.	Max.			Min.	Max.	Min.	88 300	207 000

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952357508
Diam. intérieur	65 mm
Diam. extérieur	77 mm
Épaisseur	45 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE