

## Roulement conique

### H239640-H239612CD-TIMKEN - H239640-H239612CD-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/h239640-h239612cd-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynami <sup>1)</sup> C <sub>10</sub>	Factor <sup>2)</sup> Y <sub>1</sub>	Y <sub>2</sub>	Y <sub>3</sub>	C <sub>90</sub>	Dynami <sup>3)</sup> C <sub>50</sub>	C <sub>50a</sub>	Factor <sup>4)</sup> K
mm	mm	mm	mm	N				N	N	N	
177.800	320.675	185.738	186.182	1000000	0.32	2.12	3.15	229000	140000	470000	1.63
7.000	12.625	7.3125	6.4209	410000				81100	33400	100000	

  

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight kg
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>				
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
H239640	H239612CD	3.5 0.14	202.8 7.85	1.5 0.06	301.8 11.84	28.08 1.13	16.21 0.41	95.7	93.3	0.1242	52.18 126.25				

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952360447
Diam. intérieur	177.8 mm
Diam. extérieur	320.675 mm
Épaisseur	185.738 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE