

## Roulement conique

### X32044XM-NP099132-TIMKEN - X32044XM-NP099132-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/x32044xm-np099132-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Factor <sup>(2)</sup> Y <sub>2</sub>	Dynamic <sup>(3)</sup> C <sub>90</sub>	Factor <sup>(3)</sup> K	Dynamic <sup>(4)</sup> C <sub>50</sub>	Factor <sup>(4)</sup> K	
mm	mm	mm	mm	N			N		N		
220.000	340.000	164.000	130.000	1730000	0.43	1.57	258000	1.26	100000	1.26	
8.8614	13.3858	6.4567	5.1181	385000			57900		42700		

  

Part Number		Dimensions						Pin			Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>			
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
X32044XM	NP099132	4.8	248.8	1.8	305.5	-	-	1207.8	127.4	0.1100	0.1100	0.1100	90.74	
		0.16	8.76	0.04	12.85	-	-						111.88	

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952360881
Diam. intérieur	220 mm
Diam. extérieur	340 mm
Épaisseur	164 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE