


Douille à aiguilles BHAM1212-IKO - BHAM1212-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bham1212-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g																																																			
	Standard	Mass (Ref.) g	Closed end																																																												
19.050 (3/4)	—	—	—	—	—	—	—	—	—	—	—	—																																																			
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="2">mm(inch)</th> <th colspan="2">Standard mounting dimensions</th> <th colspan="2">mm</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="2">Allowable rotational speed⁽¹⁾</th> <th colspan="2">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>f_2</th> <th>Shaft dia. h6</th> <th>Housing bore dia. J7</th> <th>Max.</th> <th>Min.</th> <th>Max.</th> <th>Min.</th> <th>N</th> <th>N</th> <th>N</th> <th>N</th> <th>rpm</th> <th colspan="2"></th> </tr> </thead> <tbody> <tr> <td>19.050</td> <td>26.988</td> <td>19.050</td> <td>1.3</td> <td>19.050</td> <td>19.037</td> <td>27.000</td> <td>26.979</td> <td>16 800</td> <td>22 600</td> <td>20 000</td> <td colspan="2">IRB 812-1</td> <td colspan="2"></td> <td colspan="2"></td> </tr> </tbody> </table>													Boundary dimensions			mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring		F_w	D	C	f_2	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	N	N	N	N	rpm			19.050	26.988	19.050	1.3	19.050	19.037	27.000	26.979	16 800	22 600	20 000	IRB 812-1					
Boundary dimensions			mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring																																																
F_w	D	C	f_2	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	N	N	N	N	rpm																																																	
19.050	26.988	19.050	1.3	19.050	19.037	27.000	26.979	16 800	22 600	20 000	IRB 812-1																																																				

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952361819
Diam. intérieur	19.05 mm
Diam. intérieur	3/4" inch
Diam. extérieur	26.988 mm
Diam. extérieur	1 1/16" inch
Epaisseur	19.05 mm
Epaisseur	3/4" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE