


## Douille à aiguilles BHAM1416-IKO - BHAM1416-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bham1416-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	<b>BHAM 1416</b>	<b>42</b>	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic	Basic static	Allowable	Assembled		
$F_w$	$D$	$C$	$r_2$	Shaft dia. $\phi_6$	Housing bore dia. $J_7$	load rating $C$	load rating $C_0$	rotational speed <sup>(1)</sup>	inner ring		
mm	mm	mm	mm	mm	mm	N	N	rpm			
22.225	30.162	25.40(1.000)	3.4	22.225 Max.	22.212 Min.	30.176 Max.	30.151 Min.	23 600	36 900	18 000	<b>IRB 1016</b>

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952361888
Diam. intérieur	22.225 mm
Diam. extérieur	30.162 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE