

## Douille à aiguilles YB1412-IKO - YB1412-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/yb1412-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
22.225 ( $\frac{7}{8}$ )	—	—	—	—	—	—	—	—	—	—	—	—	—
												<b>YB 1412</b>	<b>31</b>
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C <sub>d</sub>	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring				
F <sub>w</sub>	D	C	h <sub>6</sub> Max.	J7 Min.	J7 Max.								
22.225 $\frac{1}{2}$	28.575 $\frac{1}{2}$	19.05 $\frac{3}{4}$	—	22.225	22.212	28.587	28.566	26 300	50 700	7 000	<b>IRB 1012</b>		

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060457448
Diam. intérieur	22.225 mm
Diam. extérieur	28.587 mm
Épaisseur	19.05 mm
Poids	31 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE