

Douille à aiguilles BHAM1614-IKO - BHAM1614-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bham1614-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
25.400 (1)	—	—	—	—	—	—	—	BHAM 1614	42.5	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	t ₁ Max	Shaft dia. h _s Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.	N	N	rpm	IRB 1214	
25.400	33.338	22.22	875	3.4	25.400	25.387	33.352	33.327	23 000	37 200	15 000

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952362021
Diam. intérieur	25.4 mm
Diam. extérieur	33.338 mm
Épaisseur	22.22 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE