

Douille à aiguilles YB2416-IKO - YB2416-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/yb2416-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
38.100 (1 1/2)	—	—	—	—	—	—	—	—	YB 2416	105
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F _w	D	C	t ₁	Shaft dia. h8	Housing bore dia. J7	N	N	rpm	IRB 2016	
38.100 (1 1/2)	47.625 (1 7/8)	25.40 (1.000)	—	38.100 Max.	38.084 Min.	47.639 Max.	47.614 Min.	55 100 N	118 000 N	4 000

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952363110
Diam. intérieur	38.1 mm
Diam. intérieur	1 1/2" inch
Diam. extérieur	47.625 mm
Diam. extérieur	1 7/8" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE