

Roulement conique NA78250-78549D-TIMKEN - NA78250-78549D-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/na78250-78549d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TNA

TYPE TNA

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|--|--------------------------------------|--------------------------------------|--------------------------------------|--|--------------------------------------|-------------------------|-------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ C ₁₀ | Static ⁽²⁾ C ₀ | Factor ⁽³⁾ Y ₁ | Factor ⁽³⁾ Y ₂ | Dynamic ⁽¹⁾ C ₉₀ | Static ⁽²⁾ C ₀ | Factor ⁽³⁾ K | |
| mm | mm | mm | mm | N | N | | | N | N | N | |
| 63.500 | 139.700 | 77.788 | 91.800 | 35300 | 19500 | 0.87 | 0.78 | 1.16 | 62000 | 77000 | 91500 |
| 2.500 | 5.500 | 3.0625 | 2.236 | | | | | 11800 | 17500 | 20800 | |

| Part Number | | Shaft | | | | Housing | | | | Pin | Bearing Weight |
|-------------|--------|--|--------------------------------------|--|--------------------------------------|----------------|----------------|----|----|-------|----------------|
| Inner | Outer | Max Shaft Fillet Radius R _f | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r _h | Backing Shoulder Dia. D _s | K ₁ | K ₂ | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| NA78250 | 78549D | 2.3 | 85.8 | 1.5 | 129.9 | - | - | - | - | 6.11 | |
| | | 0.08 | 3.35 | 0.06 | 5.18 | - | - | - | - | 11.28 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952373959 |
| Diam. intérieur | 63.5 mm |
| Diam. extérieur | 139.7 mm |
| Épaisseur | 77.788 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE