

Roulement conique NA593SW-592D-TIMKEN - NA593SW-592D-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/na593sw-592d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TNASW

TYPE TNASW

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|--------|---------|---------------------------|-------------------------|-------|-------------------------------------|----------------|----------------|---------------------------------------|-----------------|------------------------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | e | Factor ¹⁾ Y ₁ | Y ₂ | C ₀ | Dynamic ²⁾ C ₉₀ | C ₅₀ | Factor ³⁾ K |
| mm | in | mm | mm | N | mm | | | | N | N | N |
| 88.900 | 3.500 | 152.400 | 82.550 | 37000 | 14000 | 0.44 | 1.53 | 2.27 | 50000 | 42400 | 57500 |
| | | | | | | | | | 12000 | 9500 | 21000 |

| Part Number | Dimensions | | | | | | Bearing Weight |
|--------------|------------|-------|-------------------------|-----------------------|---------------------------|-----------------------|----------------|
| | Inner | Outer | Shaft | | Housing | | |
| | | | Max Shaft Fillet Radius | Backing Shoulder Dia. | Max Housing Fillet Radius | Backing Shoulder Dia. | |
| | mm | mm | mm | mm | mm | mm | kg |
| | in | in | in | in | in | in | lbs. |
| NA593SW 592D | 88.9 | 152.4 | 3.5 | 104.8 | 6.8 | 146.8 | 5.81 |
| | | | 0.14 | 4.10 | 0.27 | 5.81 | 12.85 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952374734 |
| Diam. intérieur | 88.9 mm |
| Diam. extérieur | 152.4 mm |
| Épaisseur | 82.55 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE