


Roulement à aiguilles GBRI122412-IKO - GBRI122412-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri122412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 (3/4)	GBRI 122412	112	19.050 _{J0}	38.100 _{J0}	19.050 _{J0}	19.300	25.400 _{J0}
Standard mounting dimensions mm		Ball diam. mm (inch)	Basic load rating C ₀ N	Allowable rotational speed (P) rpm	Assembled inner ring		
Min.	Max.	Max.					
24	24.4	33.3	0.6 ⁽¹⁾	31 000	46 100	6 000	LRBZ 121612

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377414
Diam. intérieur	19.05 mm
Diam. extérieur	38.1 mm
Épaisseur	19.3 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE