


## Roulement à aiguilles GBRI122416-IKO - GBRI122416-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri122416-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>19.050</b> ( $\frac{3}{4}$ )	<b>GBRI 122416</b>	150	19.050 $\frac{J_3}{3}$	38.100 $\frac{J_3}{3}$	25.400 $\frac{1}{2}$	25.650	25.400 $\frac{1}{2}$

Standard mounting dimensions mm		Ball diam. mm (inch)	Basic rating $C_0$	Allowable rotational speed $(^{\circ})$ rpm	Assembled inner ring		
$d_a$	$D_a$	$r_{sm}$	$C_0$	$(^{\circ})$			
Min.	Max.	Max.	N	N			
24	24.4	33.3	0.6	41 400	67 100	6 000	LRBZ 121616

Notes: <sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377421
Diam. intérieur	19.05 mm
Diam. extérieur	38.1 mm
Épaisseur	25.65 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE