


Roulement à aiguilles GBRI203320-IKO - GBRI203320-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri203320-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
31.750 (1 1/4)	GBRI 203320	291	31.750 (1/2)	52.388 (2 1/8)	31.750 (1 1/4)	32.000	38.100 (1 1/2)
Standard mounting dimensions mm		Ball/needle lead ring C	Basic load rating C ₀	Allowable rotational speed (P)	Assembled inner ring		
d _s Min.	d _s Max.				r _{as} Max.	N	N
37	37.1	47.3	0.5	64 100	121 000	4 000	LRBZ 202420

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377476
Diam. intérieur	31.75 mm
Diam. extérieur	52.388 mm
Épaisseur	32 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE