


Roulement à aiguilles GBRI223516-IKO - GBRI223516-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri223516-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
34.925 (1 3/8)	GBRI 223516	255	34.925 (1 3/8)	55.562 (2 1/8)	25.400 (1)	25.650	41.275 (1 5/8)

Standard mounting dimensions mm		Sub-dynamic load rating C ₁₀ N	Basic static load rating C ₀ N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 222616
d _a Min.	d _a Max.				
40.2	40.2	56 600	105 000	3 500	LRBZ 222616

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377483
Diam. intérieur	34.925 mm
Diam. extérieur	55.562 mm
Épaisseur	25.65 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE