


## Roulement à aiguilles GBRI264116-IKO - GBRI264116-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri264116-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
41.275 (1 5/8)	GBRI 264116	350	41.275 (1 5/8)	65.088 (2 5/8)	25.400 (1)	25.650	50.800 (2)
Standard mounting dimensions mm		Sub-dynamic load rating C <sub>10</sub> N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed (1) rpm	Assembled inner ring		
d <sub>a</sub> Min.	d <sub>a</sub> Max.				r <sub>a</sub> Max.		
48	49	59.2	1	63 100	130 000	3 000	LRBZ 263216

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377537
Diam. intérieur	41.275 mm
Diam. extérieur	65.088 mm
Épaisseur	25.65 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE