


Roulement à aiguilles GBRI264120-IKO - GBRI264120-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri264120-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
41.275 (1 5/8)	GBRI 264120	435	41.275 (1 5/8)	65.088 (2 5/8)	31.750 (1 1/2)	32.000	50.800 (2)
Standard mounting dimensions mm		Sub-dynamic load rating C ₁₀ N	Basic static load rating C ₀ N	Allowable rotational speed (F) rpm	Assembled inner ring		
d _a Min.	d _a Max.				r _a Min.	r _a Max.	
48	49	59.2	1	74 600	162 000	3 000	LRBZ 263220

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377544
Diam. intérieur	41.275 mm
Diam. extérieur	65.088 mm
Épaisseur	32 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE