

## Roulement à aiguilles GBR445624-IKO - GBR445624-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr445624-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			$F$	$D$	$C$	$D_s$ Max.	$r_{as\ max}$
<b>69.850</b> (2 3/4)	<b>GBR 445624</b>	585	69.850 1 <sub>2</sub>	88.900 3 <sub>4</sub>	38.100 1 <sub>2</sub>	82	1.5
Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm					
125 000	273 000	2 000					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377599
Diam. intérieur	69.85 mm
Diam. extérieur	88.9 mm
Épaisseur	38.1 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE