

Roulement à aiguilles GBR607632-IKO - GBR607632-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr607632-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F_a	D	C	D_s Max.	$F_{as\ max}$
95.250 (3 3/4)	GBR 607632	1 420	95.250 (3 3/4)	120.650 (4 7/8)	50.800 (2)	112.6	1.5
Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm					
228 000	522 000	1 600					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377667
Diam. intérieur	95.25 mm
Diam. intérieur	3 3/4" inch
Diam. extérieur	120.65 mm
Diam. extérieur	4 3/4" inch
Epaisseur	50.8 mm
Epaisseur	2" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE