

Roulement à aiguilles GBR142212-IKO - GBR142212-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr142212-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F_0	D	C	D_s Max.	$r_{as\ max}$
22.225 ($\frac{9}{16}$)	GBR 142212	71	22.225 ⁽²⁾	34.925 ⁽¹⁾	19.050 ⁽²⁾	30	0.6
Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽³⁾ rpm					
28 600	40 100	7 000					

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377711
Diam. intérieur	22.225 mm
Diam. extérieur	34.925 mm
Épaisseur	19.05 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE