

Roulement à aiguilles GBR162412-IKO - GBR162412-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr162412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm ⁽¹⁾ | |
|--|---|--|------------------------------|-----------------------|-----------------------|---|---------------|
| | | | F | D | C | D_s Max. | $r_{as\ max}$ |
| 25.400 (1) | GBR 162412 | 79 | 25.400 ⁽¹⁾ | 38.100 ⁽¹⁾ | 19.050 ⁽²⁾ | 33.3 | 0.6 |
| Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽³⁾ rpm | | | | | |
| 31 000 | 46 100 | 6 000 | | | | | |

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952377735 |
| Diam. intérieur | 25.4 mm |
| Diam. extérieur | 38.1 mm |
| Épaisseur | 19.05 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE