

Roulement à aiguilles GBR263520-IKO - GBR263520-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr263520-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			\bar{F}_w	D	C	D_s Max.	$r_{as\ max}$
41.275 (1 5/8)	GBR 263520	220	41.275 (1 5/8)	55.562 (2 1/8)	31.750 (1 1/4)	50.5	0.6
Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm					
67 000	130 000	3 500					

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377810
Diam. intérieur	41.275 mm
Diam. intérieur	1 5/8" inch
Diam. extérieur	55.562 mm
Diam. extérieur	2 3/16" inch
Epaisseur	31.75 mm
Epaisseur	1 1/4" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE