

Roulement à aiguilles GBR283820-IKO - GBR283820-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr283820-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D _s Max.	r _{as max}
44.450 (1 3/4)	GBR 283820	275	44.450 (1 3/4)	60.325 (2 1/2)	31.750 (1 1/2)	55.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ N					
69 700	141 000	3 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377834
Diam. intérieur	44.45 mm
Diam. extérieur	60.325 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE