

## Roulement à aiguilles GBR303920-IKO - GBR303920-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbr303920-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			$\bar{F}_w$	D	C	$D_s$ Max.	$r_{as\ max}$
47.625 (1 7/8)	GBR 303920	250	47.625 (1 7/8)	61.912 (2 3/8)	31.750 (1 1/4)	56.2	1
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm					
N	N	N					
72 400	150 000	3 000					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377841
Diam. intérieur	47.625 mm
Diam. extérieur	61.912 mm
Épaisseur	31.75 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE