


## Roulement à aiguilles GBRI284824-IKO - GBRI284824-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri284824-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
44.450 (1 3/4)	GBRI 284824	790	44.450 (1) 1/2	76.200 (3)	38.100 (1) 1/2	38.350	57.150 (2) 1/2

Standard mounting dimensions mm		Sub-dynamic load rating C <sub>10</sub> N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed (1) rpm	Assembled inner ring		
d <sub>a</sub> Min.	d <sub>a</sub> Max.						
52.5	55	69.2	1.5	113 000	224 000	2 500	LRBZ 283624

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377872
Diam. intérieur	44.45 mm
Diam. intérieur	1 3/4" inch
Diam. extérieur	76.2 mm
Diam. extérieur	3" inch
Epaisseur	38.1 mm
Epaisseur	1 1/2" inch
Poids	514 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE