


Roulement à aiguilles GBRI325228-IKO - GBRI325228-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri325228-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
50.800 (2)	GBRI 325228	1 030	50.800 2	82.550 3 1/4	44.450 1 3/4	44.700	63.500 2 1/2

Standard mounting dimensions mm				Ball diam. mm (inch)	Basic load rating C ₀	Allowable rotational speed (P)	Assembled inner ring
d _s	D _s	r _s max	r _s min	C	C ₀	(P)	
Min.	Max.	Max.	Max.	N	N	rpm	
58	61	75.7	1.5	141 000	306 000	2 500	LRBZ 324028

Notes: (1) Maximum permissible corner radius of the housing.
(P) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377902
Diam. intérieur	50.8 mm
Diam. intérieur	2" inch
Diam. extérieur	82.55 mm
Diam. extérieur	3 1/4" inch
Epaisseur	44.45 mm
Epaisseur	1 3/4" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE