


## Roulement à aiguilles GBRI608432-IKO - GBRI608432-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/gbri608432-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>95.250</b> (3 3/4)	<b>GBRI 608432</b>	2 380	95.250 (3 3/4)	133.350 (5 1/4)	50.800 (2)	51.050	107.950 (4 1/4)
Standard mounting dimensions mm		Statically load rating $C_0$ N	Basic load rating $C_0$ N	Allowable rotational speed (1) rpm	Assembled inner ring		
$d_a$ Min.	$d_a$ Max.				$r_{as}$ Min.	$r_{as}$ Max.	
103	105	125.3	1.5	242 000	590 000	1 400	<b>LRBZ 606832</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is preapplied. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952378008
Diam. intérieur	95.25 mm
Diam. intérieur	3 3/4" inch
Diam. extérieur	133.35 mm
Diam. extérieur	5 1/4" inch
Epaisseur	50.8 mm
Epaisseur	2" inch
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE