

Roulement à aiguilles RNA69-28-U-IKO - RNA69-28-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna69-28-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
32	—	—	—	RNA 69/28U	133	32	45	30	0.3
Standard rounding dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed(2)						
43	38 900	59 100	6 000 rpm						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379074
Diam. intérieur	32 mm
Diam. extérieur	47 mm
Épaisseur	30 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE