

Roulement à aiguilles RNA49-48-UU-IKO - RNA49-48-UU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna49-48-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|--|---------------------------------------|--|---------------------------------------|---------------|---------------------|---------------------------|-----|-----|---------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r (1) |
| 55 | RNA 49/48UU | — | — | — | 187 | 55 | 70 | 22 | 0.6 |
| Standard mounting diameter D_A Max. mm | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (2) rpm | | | | | | |
| 66 | 39 600 | 66 100 | 3 500 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952379333 |
| Diam. intérieur | 55 mm |
| Diam. extérieur | 70 mm |
| Épaisseur | 22 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE