


Roulement à aiguilles RNA6910-U-IKO - RNA6910-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna6910-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
58	—	—	—	RNA 6910U	320	58	72	40	0.6
Standard mounting diameter D_s Max. mm		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)					
68		70 800	142 000	3 500 rpm					

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379388
Diam. intérieur	58 mm
Diam. extérieur	72 mm
Épaisseur	40 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE