

Roulement à aiguilles RNA6914-U-IKO - RNA6914-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna6914-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_1 (1)
80	—	—	—	RNA 6914U	910	80	100	54	1
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)						
95	76 900	143 000	2 500 rpm						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379616
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	100 mm
Diam. extérieur	3.937" inch
Epaisseur	54 mm
Epaisseur	2.126" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE