


## Roulement à aiguilles RNA4915-U-IKO - RNA4915-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna4915-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



| Shaft dia.<br>mm                                      | Identification number |                  |                |               | Mass<br>(Ref.)<br>g | Boundary dimensions<br>mm |     |     |           |
|---|-----------------------|------------------|----------------|---------------|---------------------|---------------------------|-----|-----|-----------|
|   | With two seals        | With one seal    | With two seals | With one seal |                     | $F_w$                     | $D$ | $C$ | $r_a$ (1) |
| <b>85</b>   | —                     | <b>RNA 4915U</b> | —              | —             | 520                 | 85                        | 105 | 30  | 1         |
| Standard rounding<br>dimension<br>$D_s$<br>Max.<br>mm |                       |                  |                |               |                     |                           |     |     |           |
|   | N                     | N                | N              | rpm           |                     |                           |     |     |           |
|   | 100                   | 79 600           | 153 000        | 2 000         |                     |                           |     |     |           |

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952379647 |
| Diam. intérieur | 85 mm         |
| Diam. extérieur | 105 mm        |
| Épaisseur       | 30 mm         |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE