

Roulement à aiguilles RNA6917-U-IKO - RNA6917-U-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/rna6917-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
100	—	—	—	RNA 6917U	1 300	100	120	63	1.1
Standard mounting diameter D_s Max. mm	N	N	N						
Basic dynamic load rating C	168 000	448 000	448 000	1 900					
Basic static load rating C_0									
Allowable rotational speed (2)									

Notes: (1) Minimum allowable value of chamfer dimension r_s . Allowable rotational speed applies to grease lubrication. The outer ring has an oil groove and an oil hole.
Remarks: 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379760
Diam. intérieur	100 mm
Diam. extérieur	120 mm
Épaisseur	63 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE